



Deluxe Dual Hose Shower Column

Supplied with a 3 function handset (WELS 3 star)

Over head rose is NOT supplied with the Deluxe. Purchase any shape or size rose separately. Standard size shower head thread.

2 shower hose 1.5m & 50cm

Diverter for handset or over head

Grip Turners
For turning assistance



Code	Product Description	Code	Product Description
RK-CT100	Reno Kit valve only	GTC	Grip Turner semi clear
DELUXE	Deluxe dual hose shower column	GTW	Grip Turner white
NB-CT100	New Build pack valve only	GTR	Grip Turner red
NB001	New Build Pack complete	GTB	Grip Turner blue
MF90CP	1/2" M+F chrome wall elbow	SEE WEBSITE FOR OTHER COLOURS	

- Water pressure Max 500kPa Min 100kPa
- Pressure limiting valve must be installed! Max pressure 500kPa
- Must be installed by a licenced plumber

Therm-Oz Showers Pty Ltd

ABN 22 605 703 231

Sales/Technical info@thermoz.com.au

Phone 0439 196 441 AWST


General Info 0439 992 011 AWST

accounts@thermoz.com.au



Thermostatic Showers

As seen on TV



THERM-OZ
SHOWERS PTY LTD

www.thermoz.com.au 0439 196 441 AWST

WHAT IS A THERMOSTATIC SHOWER

Thermostatic means a constant temperature, with no fluctuating hot or cold spells and no chance of scalding, making them safe and simple to use and water saving. A more efficient way to mix hot and cold water.


These products must be installed by a Licenced Plumber

THERMOSTATIC RENO KITS

Reno Kits can replace a 2 tap manual shower with no tiling or plumbing alterations. Tap spindles and shower head are replaced with components to accommodate the Thermostatic Shower mixer.

KEY FEATURES

- Can be installed horizontally or vertically
- Provides a safe constant temperature set at 38°C
- Temperature can be adjusted between 20°C - 45°C
- Supplied without shower slide rail kit
- Available in chrome
- Fits tap spacings from 80mm – 230mm
- 5 Year Warranty
- WELS Rating 3 star (9 LPM)
- WELS Reg No S13951



Old shower outlet is blanked off by chrome hanging nut



Adapters included for varying tap spacings



Therm-Oz Thermostatic Reno Kit Valve Only
Therm-Oz Deluxe Dual Hose Shower Column

Model No RK-CT100
Model No DELUXE

HOW DOES IT WORK?

Turn on with a simple 1/4 turn of the right handle. Temperature is controlled by rotating the left handle, limited to 38°C as a safety feature by an override stop button. Depressing this safety button allows the user to rotate to a higher temperature up to 45°C maximum. Rotate handle in the opposite direction for a cooler shower.



THERMOSTATIC NEW BUILD PACKS

New Build packs are for total new installations and new pipework. Supplied with a fixing bracket to locate valve in position and pipe up to.

KEY FEATURES

- For new installations and new pipework
- For new property or total refurbishment
- Supplied with fixing bracket
- Contemporary European styling
- WaterMark Licence WMK26224
- Australian Standard AS4032.4:2014
- AS/NZS3500.4:2018 Compliant
- Fully Australian Approved



Therm-Oz
Shower Kit
NB001

OR

Deluxe Dual Hose
Shower Column

150mm

Fixing Bracket



Thermostatic Shower New Build Pack including shower kit slide rail, hose and handset
Therm-Oz Thermostatic Shower New Build Pack Valve Only

Model No NB001
Model No NB-CT100